

# ELMO ESD-CC1X Keyboard Controller

# X Line



## FEATURES

- With supported 2400, 4800, & 9600 RS-232 baud rate, it controls ELMO multiplexers only
- Allows RS-232 to download update software
- 20 x 4 back light functioned LCD display, and buzzer prompt support for user friendly interface
- Time date display
- Joystick control dome's vertical/ horizontal sweep speed and direction
- Password protection supported
- Preset point edit function

# ELMO

Joy Sticker	Multi-Speed Control
Connector	RJ11, 6 pin, Female
Communication	RS232, RS485
Baud Rate	2400, 4800, 9600
Interface Specification	8 data bits, no parity, 1 stop bit
LCD Display	LCD 20 x 4
Time/ Date	RTC-IC with battery
Power Source	DC 12V 1A
Power Consumption	300mA max
Dimensions	326mm x 202mm x 80mm

**FOR USE WITH ELMO DOMES AND  
MULTIPLEXERS ONLY**

**FOR MULTI-PLATFORM USE ESD-CC2X**



**ELMO Mfg. Corp.**  
1478 Old Country Road  
Plainview, New York, 11803  
Tel. 516.501.1400  
Fax. 516.501.0429  
[www.elmousa.com](http://www.elmousa.com)

**ELMO Canada Mfg. Corp.**  
44 West Drive, Brampton,  
Ontario, L6T 3T6, Canada  
Tel. 905-453-7880  
Fax. 905-453-2391  
[www.elmocanada.com](http://www.elmocanada.com)